



Model MIX-2251AP sensor mounted in a B210LP base

Features

- Sleek, low profile design
- Photoelectric technology
- Available with additional fixed temperature detection
- Dual LEDs indicate communications and activate steady when in alarm
- Low profile base provides easy interchangeability
- Low standby current
- Rotary switches for direct-dial entry of address. Each unit can have address set for 01-159 for Advanced Protocol mode and 01-99 for CLIP mode
- Magnetic test feature
- Superior EMI protection

Description

Mircom's low profile intelligent plug-in smoke detectors with integral communications provide features that surpass conventional detectors. Sensitivity is continuously monitored and reported to the panel where the desired detector sensitivity can be programmed. Point ID capability allows each detector's address to be set with decade address switches, providing exact detector locations for selective maintenance when chamber contamination reaches an unacceptable level.

Mircom's Advanced Protocol (AP) devices use a high speed communication protocol that greatly increases the speed of communication between the intelligent devices. Mircom's Advanced Protocol uses a superior group polling method as well as an interrupt feature that provide for a faster response to an alarm condition. In addition, the Advanced Protocol allows for greater system capacity with support for up to 318 devices per SLC circuit. The AP devices are backwards compatible to operate in CLIP mode for legacy system applications.

MIX-2251AP Intelligent Photoelectric Smoke Sensor

The MIX-2251AP provides a unique optical sensing chamber that senses smoke produced by a wide range of combustion sources.

MIX-2251TAP Intelligent Photoelectric Smoke Sensor with 135°F Fixed Temperature Heat Detector

The MIX-2251TAP adds dual electronic thermistors to the MIX-2251AP to provide 135°F (57°C) fixed temperature thermal sensing.

MIX-2251TMAP Intelligent Acclimate™ Multicriteria Smoke Sensor

The MIX-2251TMAP is a photoelectric smoke detector with supplementary 135°F thermal. Also known as Acclimate™, it uses advanced on-board software to combine the signals from the photo and thermal elements. The MIX-2251TMAP is a true multicriteria detector capable of rejecting nuisance sources, but still responding quickly to real fires. Acclimate has the capability of adjusting its sensitivity according to the type of environment that it is installed in, and rate-of-rise thermal detection. These thermal detectors provide cost effective, intelligent property protection in a variety of applications.



7271-1477-0159
(MIX-1251AP)
7272-1477-0161
(MIX-2251AP/TAP/TMAP)

Specifications

Voltage Range
15 to 32 VDC
Standby Current
300 uA @ 24 VDC (one communication every 5 sec. with LED blink enabled)
LED Current (max.)
6.5 mA @ 24 VDC (on)
Height
2.0 inches (51 mm)
Diameter
6.1 inches (155 mm) installed in B210LP Base 4.1 inches (104 mm) installed in B501 Base

Shipping Weight
5.2 oz. (147 g)
Operating Humidity Range
10% - 93% non-condensing
Operating Temperature Range
MIX-2251AP: 32°F to 120°F (0°C to 49°C) MIX-2251TAP/MIX-2251TMAP: 32°F to 100°F (0°C to 38°C)
UL Listed Velocity Range
Photo/Photo with Thermal: 0 - 4000 fpm (0 - 20 m/sec) (suitable for installation in ducts)

Ordering Information

Model	Description
Intelligent Smoke Sensors	
MIX-2251AP	Intelligent Photoelectric Smoke Sensor
MIX-2251TAP	Intelligent Photoelectric Sensor with 135°F Fixed Temperature Heat Detector
MIX-2251TMAP	Intelligent Acclimate™ Multicriteria Smoke Sensor
Bases	
B501	Intelligent Flangeless Mounting Base
B210LP	Intelligent Flanged Mounting Base
B224RB	Intelligent Relay Base
B224BI	Intelligent Isolator Base
B200SR	Intelligent Standard Sounder Base (Compatible with B501BH Series)
Accessories	
RA-100Z	Remote LED Annunciator

Add suffix "A" for ULC listed model.

FOR MARKETING PURPOSES ONLY - NOT TO BE USED FOR INSTALLATION PURPOSES.



Canada
25 Interchange Way
Vaughan, Ontario L4K 5W3
Telephone: (905) 660-4655
Fax: (905) 660-4113

U.S.A.
4575 Witmer Industrial Estates
Niagara Falls, NY 14305
Toll Free: (888) 660-4655
Fax Toll Free: (888) 660-4113



Distributed by: